

PRODUCT SAFETY DATA SHEET



HEALTH · HYGIENE · HOME

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

AIR WICK Freshmatic - Cherry Blossom

1.2. Relevant identified uses of the substance or mixture and uses advised against For fragrancing and ambience / mood creation

1.3. Details of the Supplier of the Safety Data Sheet

The United Kingdom:

RB UK Hygiene Home Commercial Ltd
Wellcroft House
Wellcroft Road
Slough, Berkshire SL1 4AQ

The Republic Of Ireland:

RB Ireland Hygiene Home Commercial Ltd 7
Riverwalk
Citywest Business Campus
Dublin 24 Ireland

1.4 Emergency telephone number

RB UK Contact Telephone: 0845 769 7079

Only available during the following office hours: RB

email: consumer.relations-ukroi@rb.com **Poisons**

Information Centre of Ireland

01 809 2166 8am-10pm 7 days a week

RB ROI Contact Telephone:

09:00 - 17:00 weekdays

01 661 7318



Revision Date:

10 January 2019

Revision:

6

Replacing: 0125632605 27 Sep 2018

RB Ref No:

0117032606

Revisions: Name change and update to Data Sheet format

Additional useful information

Product Format: Aerosol can in plastic sleeve with plastic device

Storage Conditions: Store below 50°C

Proper Shipping Name: Aerosols

UN Transport Code: UN: 1950

Class & Packing Group: 2.1

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1, H222, H229

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.
See Section 16 for the full text of the H statements declared above.

SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Extremely flammable aerosol.
Pressurised container: May burst if heated.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal : Not applicable.

Hazardous ingredients : Not applicable.

Supplemental label elements : Contains Tetramethyl acetyloctahydronaphthalenes, (as 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethanone) Benzyl salicylate and Linalool. May produce an allergic reaction

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : None

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification : None known.

Recommendations : People suffering from perfume sensitivity should be cautious when using this product. Air Fresheners do not replace good hygiene practices.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
ethanol	REACH #: 01-2119457610-43 EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	≥25 - <50	Flam. Liq. 2, H225 Eye Irrit. 2, H319	[1] [2]
Butane	REACH #: 01-2119474691-32 EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	≥25 - ≤50	Flam. Gas 1, H220 Press. Gas Comp. Gas, H280	[2]
isobutane	REACH #: 01-2119485395-27 EC: 200-857-2 CAS: 75-28-5 Index: 601-004-00-0	≥10 - ≤25	Flam. Gas 1, H220 Press. Gas Comp. Gas, H280	[2]
propane	REACH #: 01-2119486944-21 EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	≥10 - ≤25	Flam. Gas 1, H220 Press. Gas Comp. Gas, H280	[2]
methanol	REACH #: 01-2119433307-44 EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X	<3	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370	[1] [2]
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl) ethanone	EC: 259-174-3 CAS: 54464-57-2	<0.25	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 1, H410 (M=1)	[1]
Benzyl salicylate	REACH #: 01-2119969442-31 EC: 204-262-9 CAS: 118-58-1	≤0.3	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1]
Linalool	REACH #: 01-2119474016-42 EC: 201-134-4 CAS: 78-70-6	≤0.3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

SECTION 5: Firefighting measures

Hazards from the substance or mixture : Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products : No specific data.

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

SECTION 6: Accidental release measures

6.4 Reference to other sections : See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

Seveso Directive - Reporting thresholds (in tonnes)

Named substances

Name	Notification and MAPP threshold	Safety report threshold
Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	50	200
Liquefied extremely flammable gases (including LPG) and natural gas	50	200
Methanol	500	5000

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P3a: Flammable aerosols containing flammable gases or flammable liquids	150	500

Do not store above the following temperature: : 50 °C

7.3 Specific end use(s)

Recommendations : Air care products Consumer uses

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
ethanol	EU OEL (Europe, 12/2011). TWA: 1000 ppm 8 hours. TWA: 1920 mg/m ³ 8 hours.
Butane	EU OEL (Europe, 7/2012). Notes: Ministry of Labour (Brochure INRS Ed 984, July 2012). Indicative exposure limits TWA: 800 ppm 8 hours. TWA: 1900 mg/m ³ 8 hours.
isobutane	EU OEL (Europe, 1/2012). TWA: 1000 ppm 8 hours. Form: gas
propane	EU OEL (Europe, 5/2010). Oxygen Depletion [Asphyxiant]. OELV-8hr: 1000 ppm 8 hours.
methanol	EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 200 ppm 8 hours. TWA: 260 mg/m ³ 8 hours.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
ethanol	DNEL	Long term Inhalation	950 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	1900 mg/m ³	Workers	Local
	DNEL	Dermal	343 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	114 mg/m ³	Consumers	Systemic
	DNEL	Long term Inhalation	950 mg/m ³	Consumers	Local
	DNEL	Dermal	206 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Oral	87 ng/kg bw/day	Consumers	Systemic
methanol	DNEL	Long term Inhalation	260 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	50 mg/m ³	Consumers	Systemic
	DNEL	Long term Dermal	8 mg/kg bw/day	Consumers	Systemic

SECTION 8: Exposure controls/personal protection

Linalool	DNEL	Long term Oral	8 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	2.8 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	16.5 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	2.5 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	15 mg/cm ²	Workers	Local
	DNEL	Short term Dermal	15 mg/cm ²	Workers	Local
	DNEL	Long term Inhalation	0.7 mg/m ³	Consumers	Systemic
	DNEL	Short term Inhalation	4.1 mg/m ³	Consumers	Systemic
	DNEL	Long term Dermal	1.25 mg/kg bw/day	Consumers	Systemic
	DNEL	Short term Dermal	2.5 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Dermal	15 mg/cm ²	Consumers	Local
	DNEL	Long term Oral	0.2 mg/kg bw/day	Consumers	Systemic
	DNEL	Short term Oral	1.2 mg/kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
ethanol	Fresh water	0.96 mg/l	Assessment Factors
	Marine water	0.79 mg/l	Assessment Factors
	Sewage Treatment Plant	580 mg/l	Assessment Factors
methanol	Fresh water sediment	3.6 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	2.9 mg/kg dwt	Equilibrium Partitioning
	Fresh water	20.8 mg/l	Assessment Factors
	Marine water	2.08 mg/l	Assessment Factors
	Sewage Treatment Plant	100 mg/l	Assessment Factors
	Fresh water sediment	77 mg/kg dwt	Equilibrium Partitioning
Linalool	Marine water sediment	7.7 mg/kg dwt	Equilibrium Partitioning
	Soil	100 mg/kg dwt	Equilibrium Partitioning
	Fresh water	0.2 mg/l	Assessment Factors
	Marine water	0.02 mg/l	Assessment Factors
	Sewage Treatment Plant	10 mg/l	Assessment Factors
	Plant		

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

SECTION 8: Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Use chemical resistant gloves classified under Standard EN374 - Protective gloves against chemicals and micro-organisms.
- Examples of preferred glove barrier materials include: Nitrile/butadiene rubber ("nitrile" or "NBR"); Chlorinated polyethylene; Butyl rubber; Polyethylene.
- Examples of acceptable glove barrier materials include: Natural rubber ("latex"); Neoprene; Viton; Ethyl vinyl alcohol laminate ("EVAL").
- A glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374) is recommended.
- Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.
- NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Considering the parameters specified by the glove manufacturer, checks during use should be carried out to ensure the gloves are still retaining their protective properties.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid. [Aerosol.]
Colour	: Colourless.
Odour	: Fragrant.
Odour threshold	: Not available.
pH	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: <34°C
Flash point	: Closed cup: <0°C
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Burning time	: Not applicable.
Burning rate	: Not applicable.
Upper/lower flammability or explosive limits	: Not available.
Vapour pressure	: Not available.
Vapour density	: Not available.
Density	: Not available.
Solubility(ies)	: Not available.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Not available.
Explosive properties	: Not available.
Oxidising properties	: Not available.
Corrosivity Remarks	: Not available.

9.2 Other information

Solubility in water	: Not available.
Type of aerosol	: Spray
Heat of combustion	: 35.42 kJ/g

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	: No specific data.

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Instability Conditions : Not available.

Instability temperature : Not available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapour	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-
butane	LC50 Inhalation Vapour	Rat	658000 mg/m ³	4 hours
isobutane	LC50 Inhalation Vapour	Rat	658000 mg/m ³	4 hours
methanol	LC50 Inhalation Gas.	Rat	145000 ppm	1 hours
	LC50 Inhalation Gas.	Rat	64000 ppm	4 hours
	LD50 Dermal	Rabbit	15800 mg/kg	-
	LD50 Oral	Rat	5600 mg/kg	-
benzyl salicylate	LD50 Oral	Rat	2227 mg/kg	-
	LD50 Dermal	Rabbit	5610 mg/kg	-
linalool	LD50 Dermal	Rat	5610 mg/kg	-
	LD50 Oral	Rat	2790 mg/kg	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value
Oral	8206.3 mg/kg
Dermal	24618.8 mg/kg
Inhalation (vapours)	246.2 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Moderate irritant	Rabbit	-	0.06666667 minutes	-
	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 microliters	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
linalool	Skin - Moderate irritant	Rabbit	-	400 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	1 hours 0.1 Milliliters	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Skin - Moderate irritant	Guinea pig	-	24 hours 100 milligrams	-
	Skin - Mild irritant	Human	-	72 hours 32 Percent	-
	Skin - Mild irritant	Man	-	48 hours 16 milligrams	-

SECTION 11: Toxicological information

	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Severe irritant	Rabbit	-	24 hours 100 milligrams	-

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Sensitisation

No known effect according to our database.

Skin : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

No known effect according to our database.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

No known effect according to our database.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

No known effect according to our database.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

No known effect according to our database.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
methanol	Category 1	Not determined	Not determined

Specific target organ toxicity (repeated exposure)

No known effect according to our database.

Aspiration hazard

No known effect according to our database.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
irritation
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing

Skin contact : No specific data.

SECTION 11: Toxicological information

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 µl/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
methanol	Acute EC50 16.912 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 3289 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 290 mg/l Fresh water	Fish - Danio rerio - Egg	96 hours
linalool	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 36.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 28.8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
linalool	-	62.4 % - Readily - 28 days	-	-

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
linalool	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
ethanol	-0.35	-	low
butane	2.89	-	low
isobutane	2.8	-	low
propane	1.09	-	low
methanol	-0.77	<10	low
benzyl salicylate	-	1170	high
linalool	2.84	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

SECTION 14: Transport information

For long distance transport of bulk material or shrunk pallet take into consideration sections 7 and 10.

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1950	UN1950	UN1950	UN1950
14.2 UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3 Transport hazard class(es)	2 	2 	2.1 	2.1 
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	<p>Limited quantity 1 L</p> <p>Special provisions 190, 327, 625, 344</p> <p>Tunnel code (D)</p>	<p>Special provisions 190, 327, 625, 344</p>	<p>Emergency schedules (EmS) F-D, S-U</p> <p>Special provisions 63, 190, 277, 327, 959, 344</p>	<p>Passenger and Cargo Aircraft Quantity limitation: 75 kg Packaging instructions: 203</p> <p>Cargo Aircraft Only Quantity limitation: 150 kg Packaging instructions: 203</p> <p>Limited Quantities - Passenger Aircraft Quantity limitation: 30 kg Packaging instructions: Y203</p> <p>Special provisions A145, A167, A802</p>

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

None of the components are listed.

SECTION 15: Regulatory information

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : None

Other EU regulations

Europe inventory : All components are listed or exempted.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Aerosol dispensers :

3



Extremely flammable

Seveso Directive

This product is controlled under the Seveso Directive.

Named substances

Name

Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas
Liquefied extremely flammable gases (including LPG) and natural gas
Methanol

Danger criteria

Category

P3a: Flammable aerosols containing flammable gases or flammable liquids

Hazard class for water : 1 Appendix No. 4

WGK: Notes : - for bulk material, not applicable for product in domestic pack sizes. Administrative Regulation on the Classification of Substances hazardous to waters into Water Hazard Classes (VwVWS)

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number

SECTION 16: Other information

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aerosol 1, H222, H229	On basis of test data

Full text of abbreviated H statements

H220 H222, H229	Extremely flammable gas. Extremely flammable aerosol. Pressurised container: May burst if heated.
H225 H280	Highly flammable liquid and vapour. Contains gas under pressure; may explode if heated.
H301 H311	Toxic if swallowed. Toxic in contact with skin.
H315 H317	Causes skin irritation. May cause an allergic skin reaction.
H319 H331	Causes serious eye irritation. Toxic if inhaled.
H370 H410 H412	Causes damage to organs. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Aerosol 1, H222, H229 Aquatic Chronic 1, H410 Aquatic Chronic 3, H412 Eye Irrit. 2, H319 Flam. Gas 1, H220 Flam. Liq. 2, H225 Press. Gas Comp. Gas, H280 Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT SE 1, H370	ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 AEROSOLS - Category 1 LONG-TERM AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE GASES - Category 1 FLAMMABLE LIQUIDS - Category 2 GASES UNDER PRESSURE - Compressed gas SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1
---	---

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.