

SAFETY DATA SHEET Astonish Wood Floor Cleaner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Astonish Wood Floor Cleaner

Product number WOOD(MIX)SEALED

Internal identification F9V2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning laminate and sealed wood floors

1.3. Details of the supplier of the safety data sheet

Supplier

The London Oil Refining Company Ltd

Astonish House Unit 1 Premier Point Staithgate Lane Bradford BD6 1DW

(01274) 767440 (office hours only)

www.astonishcleaners.com

(01274) 726285

Contact person info@astonish.co.uk

1.4. Emergency telephone number

Emergency telephone (01274) 767440 (office hours only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Eye Irrit. 2 - H319

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H319 Causes serious eye irritation.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Astonish Wood Floor Cleaner

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P264 Wash hands thoroughly after handling.

P280 Wear eye and face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/ attention.

Additional Labelling

Detergent labelling < 5% non-ionic surfactants, < 5% perfumes, < 5% soap, Contains benzyl benzoate, 1,2-

benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one

2.3. Other hazards

None

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Undecanol, branched and linear, ethoxylated (>5-15 EO)	1-5%
--	------

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Xn; R22. Xi; R41

Eye Dam. 1 - H318

 Butyl Diglycol
 1-5%

 CAS number: 112-34-5
 EC number: 203-961-6

Classification Classification (67/548/EEC or 1999/45/EC)

Eye Irrit. 2 - H319 Xi; R36

Isopropanol 1-5%

CAS number: 67-63-0 EC number: 200-661-7 REACH registration number: 01-

2119457558-25-0000

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F; R11. Xi; R36. R67

Eye Irrit. 2 - H319 STOT SE 3 - H336

C9/C11 Alcohol Ethoxylate 2.5Meo 1-5%

CAS number: -

Classification Classification (67/548/EEC or 1999/45/EC)

Eye Dam. 1 - H318 Xi; R41

Astonish Wood Floor Cleaner

1,2-benzisothiazol-3(2H)-one <1%

CAS number: 2634-33-5 EC number: 220-120-9

M factor (Acute) = 1

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Xn; R22. Xi; R38, R41. N; R50. R43

Skin Irrit. 2 - H315
Eye Dam. 1 - H318
Skin Sens. 1 - H317
Aquatic Acute 1 - H400
Aquatic Chronic 2 - H411

Citric Acid Monohydrate <1%

CAS number: 5949-29-1 EC number: 201-069-1

Classification Classification (67/548/EEC or 1999/45/EC)

Eye Irrit. 2 - H319 Xi; R36

1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2- <1%

napthyl)ethan-1-one

CAS number: 54464-57-2 EC number: 259-174-3

M factor (Chronic) = 1

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Irrit. 2 - H315 Xi; R38. N; R51/53. R43

Skin Sens. 1B - H317 Aquatic Chronic 1 - H410

2,6-dimethyloct-7-en-2-ol

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Irrit. 2 - H315 Xi; R36/38

Eye Irrit. 2 - H319

Sodium Hydroxide <1%

CAS number: 1310-73-2 EC number: 215-185-5 REACH registration number: 01-

2119457892-07-0000

Classification Classification (67/548/EEC or 1999/45/EC)

Met. Corr. 1 - H290 C; R35

Skin Corr. 1A - H314

Astonish Wood Floor Cleaner

Acetyl cedrene <1%

CAS number: 32388-55-9 EC number: 251-020-3

M factor (Chronic) = 1

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Sens. 1B - H317 N; R50/53. R43

Aquatic Chronic 1 - H410

2-methylisothiazol-3(2H)-one <1%

CAS number: 2682-20-4 EC number: 220-239-6

M factor (Acute) = 1

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 3 - H301 T; R23. Xn; R22. C; R34. N; R50. R43

Acute Tox. 3 - H311 Acute Tox. 2 - H330 Skin Corr. 1B - H314 Skin Sens. 1 - H317 STOT SE 3 - H335 Aquatic Acute 1 - H400

Aquatic Chronic 2 - H411

Sodium Carbonate <1%

CAS number: 497-19-8 EC number: 207-838-8 REACH registration number: 01-

2119485498-19-0000

Classification Classification (67/548/EEC or 1999/45/EC)

Eye Irrit. 2 - H319 Xi; R36

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Remove exposure and give water to drink if mouth irritation experienced. Seek medical advice

if recovery not rapid.

Ingestion Drink water. If symptoms persist seek medical advice.

Skin contact Rinse affected area with water.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Possible mild irritation of breathing passage and possible mouth irritation.

Ingestion Possible mild stomach upset and mild soreness of mouth.

Skin contact Possible mild transient irritation of skin.

Eye contact Causes eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

No data available

Specific treatments

No data available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

Specific hazards Product does not support combustion, minimal fire hazard. Minimal quantities of oxides of

carbon may be produced.

5.3. Advice for firefighters

Protective actions during

firefighting

Use protection suitable to cause of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Product is intended to be rinsed away to sewer after use. For bigger spillages non-household

spillages prevent entry into sewer or drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb household spillages with e.g kitchen roll and dispose of in bin. Wipe affected area

clean with a damp cloth.

6.4. Reference to other sections

Reference to other sections None

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautionsUse as instructed on label. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in ambient conditions. Keep out of the reach of children.

7.3. Specific end use(s)

Specific end use(s) Cleaning wood floors

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Butyl Diglycol

Long-term exposure limit (8-hour TWA): 10 ppm 67.5 mg/m³ Short-term exposure limit (15-minute): 15 ppm 101.2 mg/m³

Isopropanol

Long-term exposure limit (8-hour TWA): EH40 WEL, WEL 400 ppm 999 mg/m^3 Short-term exposure limit (15-minute): EH40 WEL 500 ppm $1,250 \text{ mg/m}^3$

1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-napthyl)ethan-1-one

Long-term exposure limit (8-hour TWA): DNEL 0.1011 mg/cm3 Dermal Long-term exposure limit (8-hour TWA): DNEL 1.76 mg/m³ Inhalation Long-term exposure limit (8-hour TWA): DNEL 1.73 mg/kg Dermal

2,6-dimethyloct-7-en-2-ol

Long-term exposure limit (8-hour TWA): DNEL 73.5 mg/m3 Inhalation Long-term exposure limit (8-hour TWA): DNEL 20.8 mg/kg Dermal

Sodium Hydroxide

Short-term exposure limit (15-minute): WEL 2 mg/m³

Acetyl cedrene

Long-term exposure limit (8-hour TWA): DNEL 1.175 mg/m³ Inhalation Long-term exposure limit (8-hour TWA): DNEL 0.333 mg/kg Dermal

Sodium Carbonate

Long-term exposure limit (8-hour TWA): 10 mg/m³

WEL = Workplace Exposure Limit

Citric Acid Monohydrate (CAS: 5949-29-1)

- Fresh water; 0.44 mg/l **PNEC**

> - Sediment (Freshwater); 3.46 mg/kg - Sediment (Marinewater); 34.6 mg/kg

- Marine water; 0.044 mg/l

- STP; >1000 mg/l - Soil; 33.1 mg/kg

8.2. Exposure controls

Environmental exposure This product does not pose a hazard in normal use when following the usage instructions.

controls Take care to avoid contact with skin and eyes.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Clear thin pink/red liquid **Appearance**

Pink/Red Colour Odour Fruity/Floral Odour threshold Not known.

pН pH (concentrated solution): 7.5 - 9.2

Melting point Not known.

Initial boiling point and range Not measured (>100°C)

Flash point Not determined.

Evaporation rate Not known. Not known. **Evaporation factor**

Flammability (solid, gas) Does not ignite.

Upper/lower flammability or

explosive limits

Does not ignite.

Other flammability Not relevant.

Astonish Wood Floor Cleaner

Vapour pressure Not determined.

Vapour density 1 (Air=1)

Relative density 1.000 - 1.020

1.000 - 1.020 @ 20°C

Not determined.

Bulk density Not relevant.

Solubility(ies) Soluble in water

Partition coefficient Not known.

Auto-ignition temperature Not known.

Decomposition Temperature Not available.

Explosive properties None

Explosive under the influence

of a flame

Viscosity

Not considered to be explosive.

Oxidising properties Not applicable.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No reactivity hazards expected.

10.2. Chemical stability

Stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

None under normal conditions.

10.4. Conditions to avoid

Conditions to avoid None known.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Hazardous decomposition Carbon

products

Carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects This mixture has not been tested. Based on the available data of the ingredients the

classification criteria are not met.

Acute toxicity - oral

ATE oral (mg/kg) 16,470.59

Astonish Wood Floor Cleaner

Undecanol, branched and linear, ethoxylated (>5-15 EO)

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

350.0

Species Rat

350.0 ATE oral (mg/kg)

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,001.0

mg/kg)

Species Rat

2,001.0 ATE dermal (mg/kg)

Butyl Diglycol

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

2,000.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.0

mg/kg)

Species Rabbit

Isopropanol

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

5,820.0

Species

Rat

ATE oral (mg/kg)

5,820.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 12,800.0

mg/kg)

Species Rabbit

ATE dermal (mg/kg) 12,800.0

C9/C11 Alcohol Ethoxylate 2.5Meo

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

2,000.0

Rat

Species

1,2-benzisothiazol-3(2H)-one

Astonish Wood Floor Cleaner

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

2,660.0

Species Acute toxicity estimate

ATE oral (mg/kg) 500.0

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity

The mixture has not been tested. Based on the avaliable data of the ingredients the classification criteria are not met.

Undecanol, branched and linear, ethoxylated (>5-15 EO)

Acute toxicity - fish LC₅₀, 96 hours: >1 - 10 mg/l, Cyprinus carpio (Common carp)

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: >1 - 10 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅o, 72 hours: >1 - 10 mg/l, Desmodesmus subspicatus

Butyl Diglycol

Acute toxicity - fish LC₅₀, : 100 mg/l, Algae

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: >100 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, : 100 mg/l, Desmodesmus subspicatus

Isopropanol

Acute toxicity - fish LC₅₀, 96 hours: 9640 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 13299 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅o, 72 hours: 1.000 mg/l, Desmodesmus subspicatus

Acute toxicity - microorganisms

EC₅₀, : >1000 mg/l, Activated sludge

C9/C11 Alcohol Ethoxylate 2.5Meo

Acute toxicity - fish LC₅₀, 96 hours: 1-10 mg/l, Algae

1,2-benzisothiazol-3(2H)-one

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute) 1

12.2. Persistence and degradability

Astonish Wood Floor Cleaner

Persistence and degradability Does not contain any components considered to be persistent. Contains detergents that

satisfy the biodegradation requirements of directive 648/2004/EC.

Butyl Diglycol

Biodegradation - Degradation 76: 28 days

Degradation 90-100: 8 daysDegradation 90-100: 14 days

Isopropanol

Biodegradation - Degradation 95: 21 days

12.3. Bioaccumulative potential

Bioaccumulative potentialNo bio-accumulative potential noted for any component.

Partition coefficient Not known.

12.4. Mobility in soil

Mobility The components of the mixture are readily absorbed into soil and are mobile in water

environment.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

No data available.

Butyl Diglycol

Results of PBT and vPvB This product does not contain any substances classified as PBT or vPvB. assessment

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of according to local regulations. Avoid disposing into drainage systems and into the

environment. Dispose of contaminated packaging in the same way as the product itself. Non-

contaminated packages may be recycled.

SECTION 14: Transport information

General Not regulated.

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not regulated.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation This safety data sheet is compliant with EC Regulation 1907/2006 (REACH) as adapted by

453/2010, Directive 67/548/EEC and EC Regulation 1272/2008 (CLP).

Dangerous Preparations Directive 1999/45/EC.

Regulation (EC) No. 648/2004 of the European Parliament and of the Council of 31st March

2004 on detergents.

15.2. Chemical safety assessment

SECTION 16: Other information

Abbreviations and acronyms ATE: Acute Toxicity Estimate.

used in the safety data sheet CAS: Chemical Abstracts Service.

DNEL: Derived No Effect Level.

LC₅₀: Lethal Concentration to 50 % of a test population.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative. PNEC: Predicted No Effect Concentration.

EC₅₀: 50% of maximal Effective Concentration.

Revision comments Updated Supplier Information

Issued by The London Oil Refining Company Ltd

Revision date 22/05/2017

Revision 9.2

Supersedes date 12/03/2015

SDS number 4993

Risk phrases in full R11 Highly flammable.

R22 Harmful if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R35 Causes severe burns.

R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R50 Very toxic to aquatic organisms.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

H225 Highly flammable liquid and vapour.

H290 May be corrosive to metals.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.