# **PRODUCT SAFETY DATA SHEET**



#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

MR SHEEN Multi-surface Aerosol Spring Fresh

# 1.2. Relevant identified uses of the substance or mixture and uses advised against Aerosol Polish

#### 1.3. Details of the Supplier of the Safety Data Sheet

The United Kingdom: RB UK Commercial Ltd

Wellcroft House

Wellcroft Road

Slough

Berkshire SL1 4AQ The Republic Of Ireland:
Reckitt Benckiser Ireland Ltd

7 Riverwalk

Citywest Business Campus

Dublin 24 Ireland

1.4 Emergency telephone number

RB UK Contact Telephone: 0845 769 7079 RB ROI Contact Telephone: 01 661 7318

Only available during the following office hours: 09:00 - 17:00 weekdays

RB Contact Email: consumer.relations-ukroi@rb.com

Poisons Information Centre of Ireland: 01 809 2166 8am-10pm 7 days a week

 Revision Date:
 Revision
 Replacing
 RB Ref No:

 1 March 2017
 7
 4532236806 01 Mar 2016
 4532244107

**Revisions:** Correction to product name

Additional useful information

**Product Format:** Aerosol

UN Transport Code UN: 1950 Class & Packing Group 2.1

Proper Shipping Name Aerosols

Store below 50°C

**(i)** 



### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1, H222, H229 Aquatic Chronic 3, H412

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : F+; R12

R52/53

Physical/chemical

**Environmental hazards** 

hazards

: Extremely flammable.

: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See Section 16 for the full text of the R phrases or H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms

Signal word Danger

Hazard statements : Extremely flammable aerosol.

Harmful to aquatic life with long lasting effects. Pressurized container: may burst if heated.

Precautionary statements

General : Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

Use only as directed

Prevention Do not pierce or burn, even after use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking

Do not spray on an open flame or other ignition source. Do not pierce or burn, even

after use.

Response : Not applicable.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

: Not applicable. Disposal

Hazard symbol or symbols



Indication of danger

Risk phrases

: Extremely flammable

: R12- Extremely flammable.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases : S2- Keep out of the reach of children.

S16- Keep away from sources of ignition - No smoking.

S23- Do not breathe spray. S25- Avoid contact with eyes.

S26- In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S28- After contact with skin, wash immediately with plenty of soap and water. S46- If swallowed, seek medical advice immediately and show this container or

S51- Use only in well-ventilated areas.



Hazardous ingredients

(DPD)

Hazardous ingredients

(CLP)

: Not applicable.

: Not applicable.

Supplemental label elements (DPD)

: Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No

smoking. Keep out of the reach of children.

Supplemental label elements (CLP) : Contains Chloromethylisothiazolinone. May produce an allergic reaction. Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Special packaging requirements

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification

: None known.



# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Substance/mixture : Mixture

			Classification		
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
Hydrocarbons, C8-C9, isoalkanes	REACH #: 01-2119548395-31	10 - 15	R10	Flam. Liq. 3, H226	[1]
EC: 932-020-9	EC: 932-020-9		Xn; R65	STOT SE 3, H335 (Respiratory tract irritation)	
			N; R51/53	Asp. Tox. 1, H304 Aquatic Chronic 2, H411	
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	5 - 10	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
isobutane	EC: 200-857-2 CAS: 75-28-5 Index: 601-004-00-0	2.5 - 5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	< 2.5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
			See Section 16 for the full text of the R- phrases declared above.	See Section 16 for the full text of the H statements declared above.	

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.



### **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention if irritation occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur. Wash clothing before reuse.

Clean shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air

and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

as a collar, tie, belt or waistband.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.
Ingestion : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.



# **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

: None known.

media

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.



### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

# 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

### Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

#### Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

#### 6.4 Reference to other sections

 See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information



# **SECTION 7: HANDLING AND STORAGE**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# 7.2 Conditions for safe storage, including any incompatibilities

Storage

: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

#### 7.3 Specific end use(s)

Recommendations

: Polishes and wax blends

Consumer uses

Industrial sector specific

solutions

: Not available



### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
Europe	
butane	EU OEL (Europe, 7/2012). Notes: Ministry of Labour (Brochure INRS Ed 984, July 2012). Indicative exposure limits TWA: 800 ppm 8 hours. TWA: 1900 mg/m³ 8 hours.
isobutane	EU OEL (Europe, 1/2012). TWA: 1000 ppm 8 hours. Form: gas
propane	EU OEL (Europe, 5/2010). Oxygen Depletion [Asphyxiant]. OELV-8hr: 1000 ppm 8 hours.

# procedures

Recommended monitoring : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### 8.2 Manufacturer: Exposure controls

#### Appropriate engineering controls

 Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosionproof ventilation equipment.

# Individual protection measures

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

# Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

Permeation level 6, Penetration level 3 following EN374, taking into consideration the exposure of chemicals given in chapter 3.



#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

# Other skin protection

 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.



# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid. [Aerosol.]

Colour : Colourless. Odour : Characteristic. : Not available. Odour threshold pΗ : Not available. Melting point/freezing point : Not available.

Initial boiling point and

boiling range

: <34°C

Flash point : Closed cup: <0°C : Not available. Evaporation rate : Not available. Flammability (solid, gas) **Burning time** : Not applicable. : Not applicable. **Burning rate** 

Upper/lower flammability or

explosive limits

: Not available.

Vapour pressure : Not available. : Not available. Vapour density : 0.883 g/cm3 [20°C] Density Solubility(ies) : Not available.

Partition coefficient: n-octanol/ : Not available.

Decomposition temperature : Not available. Viscosity : Not available. **Explosive properties** : Not available. : Not available. Oxidising properties Corrosivity Remarks : Not available.

9.2 Other information

Aerosol product

Type of aerosol : Spray Heat of combustion 5.411 kJ/g

No additional information.



# **SECTION 10: STABILITY AND REACTIVITY**

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products Instability Conditions  Under normal conditions of storage and use, hazardous decomposition products should not be produced.

: Not available.

Instability temperature : Not available.



# **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
butane isobutane	LC50 Inhalation Vapour LC50 Inhalation Vapour	I		4 hours 4 hours

#### Acute toxicity estimates

Not available

#### Irritation/Corrosion

No known effect according to our database.

#### Sensitisation

No known effect according to our database.

#### Mutagenicity

No known effect according to our database.

#### Carcinogenicity

No known effect according to our database.

#### Reproductive toxicity

No known effect according to our database.

#### Teratogenicity

No known effect according to our database.

# Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C8-C9, isoalkanes	Category 3		Respiratory tract irritation

# Specific target organ toxicity (repeated exposure)

No known effect according to our database.

### Aspiration hazard

Product/ingredient name	Result	
Hydrocarbons, C8-C9, isoalkanes	ASPIRATION HAZARD - Category 1	

# Potential acute health effects

 Eye contact
 : No known significant effects or critical hazards.

 Inhalation
 : No known significant effects or critical hazards.

 Skin contact
 : No known significant effects or critical hazards.

 Ingestion
 : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.
Ingestion : No specific data.



# Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

# Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. Teratogenicity Developmental effects : No known significant effects or critical hazards. Fertility effects : No known significant effects or critical hazards.

Other information : Not available.



# **SECTION 12: ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

No known effect according to our database.

#### 12.2 Persistence and degradability

No known effect according to our database.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
butane	2.89	-	low
isobutane	2.8	-	low
propane	1.09	-	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc) : Not available.

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### Product

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: The classification of the product may meet the criteria for a hazardous waste.

**Packaging** 

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered

when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.



# **SECTION 14: Transport Information**

For long distance transport of bulk material or shrunk pallet take into consideration sections 7 and 10.

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1950	UN1950	UN1950	UN1950
14.2 UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3 Transport hazard class(es)	2	2	2.1	2.1
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	Limited quantity	Limited quantity	Limited quantity	See DG list

# **SECTION 15: REGULATORY INFORMATION**

Chemical Safety Assessment following regulation 1907/2006/EC: Not relevant.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Integrated pollution : Not listed

prevention and control

list (IPPC) - Air

Integrated pollution : Not listed

prevention and control list (IPPC) - Water

CMR Substances

None of the components are listed.

Aerosol dispensers :

3



Extremely flammable

Hazard class for water : 2 Appendix No. 4

15.2 Chemical Safety Assessment : Not applicable.



# **SECTION 16: OTHER INFORMATION**

Abbreviations and acronyms : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation (Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Key literature references and sources for data : Not available.

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1, H222, H229 Aguatic Chronic 3, H412

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Aerosol 1, H222, H229	On basis of test data	
Aquatic Chronic 3, H412	Calculation method	

Europe

Full text of abbreviated H statements : H220 Extremely flammable gas.

H222, Extremely flammable aerosol. Pressurized container: may burst if heated.

H229

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation. (Respiratory tract irritation)

(Respiratory tract irritation)

H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

: Aerosol 1, H222, H229 AEROSOLS - Category 1

Aquatic Chronic 2, H411 LONG-TERM AQUATIC HAZARD - Category 2 Aquatic Chronic 3, H412 LONG-TERM AQUATIC HAZARD - Category 3

Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1 Flam. Gas 1, H220 FLAMMABLE GASES - Category 1 FLAMMABLE LIQUIDS - Category 3

Press. Gas Comp. Gas, GASES UNDER PRESSURE - Compressed gas

H280

STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE (Respiratory tract EXPOSURE) (Respiratory tract irritation) - Category 3

irritation)

Full text of abbreviated R phrases

: R12- Extremely flammable.

R10- Flammable.

R65- Harmful: may cause lung damage if swallowed.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications

[DSD/DPD]

: F+ - Extremely flammable

Xn - Harmful

N - Dangerous for the environment

This document complements the technical usage instructions but does not replace them. The information contained herein is based on our best current knowledge of the product concerned, and is given in good faith. The attention of recipients is drawn to (amongst other things) the element of risk consequent to use of the product other than that for which it was intended.

In no way does this document remove the need of the recipient of the product to fully understand and apply statutory requirements. It is the recipient's sole responsibility to take due precautions relative to the use made of the product. All



information contained herein is only to assist the recipient in fulfilling their statutory duty connected with the use of hazardous materials.

This Document may be entitled <u>Product Safety Data Sheet</u> as required by REACH (Registration, Evaluation, Authorisation and restriction of Chemicals) Annex II OR <u>Product Data Information Sheet</u> where a product is not required to be supported by a full REACH compliant SDS (e.g. not classified as hazardous or out of scope, such as cosmetics). Changes from the previous version are given in Section 1.

This list of information must not be considered as exhaustive, and does not exonerate the recipient from taking other precautions described in documents other than those mentioned, concerning the storage and use of the product, for which they remain the sole person responsible.